



Revillusion® 30" Built-in Electric Firebox

RBF30WC Weathered Concrete





Mood-maker Remote Customize the light

Customize the light color and intensity for a fireplace that reflects your personality.

120 V | 1,300 W | 4,400 BTU 208 V | 1,975 W | 6,745 BTU 240 V | 2,575 W | 8,794 BTU



Model #	Description	Lbs / Kg	UPC	Wty⁺	Carton Dimensions (WxHxD)		Cube	
					Inches	cm	ft³	m³
RBF30WC	30" Built-in Electric Firebox - Weathered concrete interior	67.7 / 30.7	781052 129849	2 yrs.	35-1/4 x 15 x 31-5/8	89.8 x 38.2 x 80.4	9.7	0.3
RBF30	30" Built-in Electric Firebox - Herringbone brick interior	67.7 / 30.7	781052 104747	2 yrs.	35-1/4 x 15 x 31-5/8	89.8 x 38.2 x 80.4	9.7	0.3
RBFL30BR	Birch Log Set	15 / 6.8	781052 130012	2 yr.	25-7/8 x 17-1/2 x 15	65.5 x 44.2 x 38.1	3.90	0.11
RBFL30FC	Fresh Cut Log Set	15 / 6.8	781052 129962	2 yr.	25-7/8 x 17-1/2 x 15	65.5 x 44.2 x 38.1	3.90	0.11
RBFPLUG	Plug Kit	0.6 / 0.3	781052 107656	1 yr.	7 x 3 x 4	17.8 x 7.6 x 10.2	0.05	0.00
RBFGLASS30	Single Glass Pane	22.1 / 10.0	781052 108004	1 yr.	35-5/8 x 29-1/4 x 4-1/4	90.4 x 74.2 x 10.6	2.6	0.07
RBFDOOR30	30" Glass Door	28.4 / 12.8	781052 108042	1 yr.	35-7/8 x 30-1/8 x 4-5/8	91.3 x 76.4 x 11.6	2.9	0.08
RBF30TRIM38	38" Installation Trim	14.0 / 6.4	781052 123625	1 yr.	41-1/8 x 35-7/8 x 4-5/8	104.3 x 91.2 x 11.8	3.7	0.01
RBF30TRIM44	44" Installation Trim	19.4 / 8.8	781052 123601	1 yr.	47-1/8 x 38-7/8 x 4-5/8	119.5 x 98.8 x 11.8	4.7	0.01

 $Specifications, finishes and dimensions are subject to change. \ ^1Limited warranty. \ @2019 \ Glen \ Dimplex \ Americas.$

Features

Revillusion® Flame Technology
Flames are larger, brighter and more random, appearing from within the logs.

Mirage™ Flame Panel
Partially frosted acrylic panel is clearly
better than a mirror, showing only
dazzling flames and no reflections.

ThruView™ Full-depth Design See clear through the flames to the back of the firebox for a more authentic experience.

Mood Lighting
Customize the firebox glow with a choice of warm hues, plus midnight mode.

Color Enhancement
Adjust the flame base color to red or blue.

Realogs® Plus

A full grate of life-size hardwood-cast logs, tiered for greater depth.

Full Surround Firebox

More authentic day or night;

270-degree surround with natural soot markings.

Adjust light level to suit the room and choose flicker effect for enhanced firelight.

Ambient Light Sensor

Automatically adjusts firebox light to suit the room day to night.

Quick and Easy Installation Simply frame, wire and finish – no venting, gas lines or safety screens.

Primary Heat
Option to use 240 volt supply for up
to 8,800 BTU - use as part of primary
heating plan; heater also operates
without flame and can be deactivated.

All-season Flames
Enjoy the unique charm of a fireplace
365 days a year using the flames
without the heat.

Direct-wire
Designed to be direct-wired to a 120, 208 or 240 volt circuit for a seamless look (optional plug kit available).

Low Carbon Footprint
The most sustainable fireplace option; no emissions and 100% efficient.